

DATASHEET

SIRIUS



GENERAL

Art.Nr:	A-050
GTIN:	4030281286943
E-class number:	40-02-01-06
Customs tariff number:	84798997

Standards:	ANSI Z359.4:2013, DIN EN 12841-C: 2006,DIN EN 15151- 1:2012,DIN EN 341- 2A:2011
Net weight:	0.51 kg
Gross weight:	0.51 kg

DATASHEET

SIRIUS

SIRIUS packs the advantages of the best descenders for industrial and rescue applications into an extremely compact design - for better handling and long service life. SIRIUS lies perfectly in your hand. The auto-returning operating lever has a particularly small radius of motion so that you can work fast, accurately, more comfortably and safely. During rope insertion, which is intuitive and simple, the carabiner on the harness can stay connected to the device. We designed the route of the rope in such a way that it is protected from twisting and kinking, and from excessive wear and tear. SIRIUS was developed for extended use under the toughest of conditions. That's why it is made of up to 100 % metal - without any vulnerable synthetic spots. SIRIUS. Best ergonomics and long service life in its most compact form: - Outstanding handling thanks to compact design and intuitive route of the rope - Long-lasting and sturdy: 100% metal - Auto-locking function, improved an

FEATURES

Application areas:	Various
Colour:	Black
Lifting function:	No
Max. Abseil speed:	2.00 m/s
Maximum compatible rope diameter:	12.00 mm
Maximum load 1 person:	141.00 kg
Maximum load 2 persons:	250.00 kg
Maximum lifetime:	30 years
Maximum number of persons:	2
Maximum load:	250.00 kg
Maximum temperature:	60 °C
Minimum compatible rope diameter:	9.00 mm
Minimum temperature:	-30 °C
Panic function:	Yes
Rescue function:	Yes

MATERIAL

Material:	Aluminium, Steel
-----------	------------------